




*from 09/18
**before 09/18



VD

86.3216.00.2 (x8) (M10*)
[44Nm-32.4Lbft]
 86.2562.00.2 (x8) (M8**) **[22Nm-16.2Lbft]**
 48.0034.09.2 (with M10*)
 48.0003.09.2 (with M8**)

39.0007.41.2
 41.0033.26.2
 81.2913.00.2

80.2178.10.2□
 80.1369.00.2

VM

86.3216.00.2 (x8) (M10*)
[44Nm-32.4Lbft]
 86.2562.00.2 (x8) (M8**) **[22Nm-16.2Lbft]**
 39.0021.09.2 (with M10*)
 39.0008.09.2 (with M8**)

39.0010.54.2
 40.0017.26.2
 81.3023.00.2

80.2264.10.2◇

VP

86.3216.00.2 (x8) (M10*)
[44Nm-32.4Lbft]
 86.2562.00.2 (x8) (M8**) **[22Nm-16.2Lbft]**
 48.0034.09.2 (with M10*)
 48.0003.09.2 (with M8**)

80.6579.00.2
 41.0146.26.2
 39.0017.76.2
 81.2912.00.2

41.0206.19.2
 80.2178.10.2□
 80.1369.00.2

VC (only PPS 1212)

86.3216.00.2 (x8) **[44Nm-32.4Lbft]**
 86.2683.00.2 (x8) **[22Nm-16.2Lbft]**
 39.0021.09.2

39.0010.54.2
 40.0031.26.2
 81.3023.00.2

32.0098.07.2
 80.2264.10.2◇

OPTIONAL FRONT

36.9814.97.3

 31.1466.32.2
 84.3560.00.2(x3)
 84.1846.00.2(x3)

REAR

31.1482.32.2

 31.1966.61.2(x2) included
 86.2547.00.2 (x2)

SAFETY VALVE

24.3040.97.3

*from 09/18
 **before 09/18

KIT MEMBRANE - DIAPHRAGMS KIT					KIT VALVOLE - VALVES KIT		KIT POMPA - PUMP KIT		
BUNA-N	DURAMAX	HPS	PENTAX	VITON	/		VD-VP	VM-VC	
STD.	OPT.	OPT.	OPT.	OPT.	STD.				
39.9802.97.3	39.9803.97.3DS	39.9804.97.3	39.9811.97.3	39.9805.97.3	39.9808.97.3		39.9806.97.3	39.9809.97.3	
■	▲	▼	◆	◼	○		□	◇	

INFORMAZIONI UTILI - USEFUL INFORMATION				
OLIO - OIL	OLIO MOTORE O SEMIIDRAULICO SAE 75-W90 MOTOR OIL OR SEMI-HYDRAULIC OIL SAE 75-W90			
PRESSIONE DI LAVORO OPERATING PRESSURE	2 ÷ 5	5÷10	10 ÷ 20	20 ÷ 50
ACCUMULATORE	2	2 ÷ 5	5 ÷ 7	6 ÷ 8