



# 3"PG-W 1" Series

## 3PG 4025-W



10.6 l/m  
2.8 USGPM



max 280 BAR  
4060 P.S.I.

CODICE CODE	MODELLO MODEL	Press. Max Max Pres.		RPM 2800				RPM 3000				RPM 3450				Pist. Plung.	Corsa Stroke
				Portata-Flow		Potenza-Power		Portata-Flow		Potenza-Power		Portata-Flow		Potenza-Power			
		BAR	P.S.I.	L/min	GPM	KW	HP	L/min	GPM	KW	HP	L/min	GPM	KW	HP	Dia. mm	mm
02.7050.97.3	3PG 4040-W	280	4060	13,3	3,5	7,3	9,8	14,2	3,8	7,8	10,5	16,1	4,2	8,8	11,8	13	13
02.7051.97.3	3PG 4035-W	280	4060	11,7	3,1	6,4	8,6	12,5	3,3	6,9	9,2	14,1	3,7	7,7	10,4	13	11,4
02.7052.97.3	3PG 4030-W	280	4060	10,0	2,6	5,5	7,4	10,7	2,8	5,9	7,9	12,1	3,2	6,7	8,9	13	9,8
02.7053.97.3	3PG 4025-W	280	4060	8,8	2,3	4,8	6,5	9,4	2,5	5,2	7,0	10,6	2,8	5,8	7,8	13	8,6

Con valvola depressurizzatrice incorporata e eiettore detergente regolabile.  
With unloader valve and adjustable injector built-in.