

Regolatori di pressione / Pressure regulators

VS 280 – VS 400 (80 L/Min-400 BAR)

VS 280 – VS 400 (80 L/Min-400 BAR)



80 l/min
21 USGPM



max 400 BAR
5800 P.S.I.

APPLICAZIONI - APPLICATIONS



AGRICOLTURA
AGRICULTURE



SPRAYER
SPRAYER



DISINFESTAZIONE
DISINFESTATION



ATOMIZZATORI
ATOMIZERS



VALVOLE DI SICUREZZA
SAFETY VALVES
SOUPAPES DE SÉCURITÉ
VÁLVULAS DE SEGURIDAD

Temperatura max: 90°C 195°F
Max temperature: 90°C 195°F
Température maxi: 90°C 195°F
Temperatura máx: 90°C - 195°F

VS 280 – VS 400									
Cod. Part Number	Modello Model	Pressione Max Max Pressure		Portata Flow		Attacco pompa Port size	Scarico By-pass	Peso Weight	
		bar	psi	l/min	GPM			Kg	lbs
86.1677.00.2	VS 280 (AISI 303)	280	4000	80	21	N°2 1/2 BSP – F	1/2 BSP – F	1.21	2.7
86.1678.00.2	VS 400 (AISI 303)	400	5800	80	21	N°2 1/2 BSP – F	1/2 BSP – F	1.21	2.7
ACCIAIO INOX - STAINLESS STEEL									