







VALVOLE

VALVOLE REGOLAZIONE PRESSIONE UNIFIT CON BY-PASS ESTERNO
 UNLOADER VALVES UNIFIT WITH EXTERNAL BY-PASS
 RÉGULATEURS DE PRESSION UNIFIT
 VÁLVULAS DE REGULACIÓN DE PRESIÓN UNIFIT

TEMPERATURA MAX: 60°C - 140°F
 MAX TEMPERATURE: 60°C - 140°F
 TEMPÉRATURE MAXI: 60°C - 140°F
 TEMPERATURA MÁX: 60°C - 140°F

	CODICE PART NR.	Uscita Outlet	Modello Model	Pressione Max Max Pressure		Inj. Dia.	Portata Flow		Attacco pompa Port size	Entrata Inlet	Peso Weight		
				bar	psi		l/min	GPM			BSP	BSP	Kg
 UNIFIT 20	05.8730.97.3	3/8 BSP-M	UNIFIT 20	140	2000	/	30	8.0	3/8 - M	3/8 - M	0.6	1.3	
	05.8733.97.3	22x1.5-M									0.64	1.4	
 UNIFIT.I 20	UNIFIT - UNIFIT.I 20 ORANGE COLOR	05.8731.97..	3/8 BSP-M	UNIFIT.I 20 Fixed injector	140	2000	/	9.5	2.5	3/8 - M	3/8 - M	0.64	1.4
												18	11
		05.8734.97..	22x1.5-M	21	15	4.0	0.68	1.5					
				23	21	5.5	0.68	1.5					
 UNIFIT.I 20 Adj. UNIFIT.ES 20	UNIFIT - UNIFIT.I 20 ORANGE COLOR	05.8732.97..	3/8 BSP-M	UNIFIT.I 20 Adj. injector	140	2000	/	9.5	2.5	3/8 - M	3/8 - M	0.64	1.4
												18	11
		05.8735.97..	22x1.5-M	21	15	4.0	0.68	1.5					
				ES	11	2.9	0.68	1.5					
 UNIFIT 30	05.8736.97.3	3/8 BSP-M	UNIFIT 30	210	3000	/	30	8.0	3/8 - M	3/8 - M	0.6	1.3	
	05.8739.97.3	22x1.5-M									0.64	1.4	
 UNIFIT.I 30	UNIFIT - UNIFIT.I 30 BLUE COLOR	05.8737.97..	3/8 BSP-M	UNIFIT.I 30 Fixed injector	210	3000	/	9.5	2.5	3/8 - M	3/8 - M	0.64	1.4
												18	11
		05.8740.97..	22x1.5-M	21	15	4.0	0.68	1.5					
				23	21	5.5	0.68	1.5					
 UNIFIT.I 30 Adj. UNIFIT.ES 30	UNIFIT - UNIFIT.I 30 BLUE COLOR	05.8738.97..	3/8 BSP-M	UNIFIT.I 30 Adj. injector	210	3000	/	9.5	2.5	3/8 - M	3/8 - M	0.64	1.4
												18	11
		05.8741.97..	22x1.5-M	21	15	4.0	0.68	1.5					
				ES	11	2.9	0.68	1.5					

.. Aggiungere al codice - Add to the last number - Ajouter à la réf. - Añadir a la ref.:

16: valvola con ugello eiettore dia. 1.6mm - valve with injector nozzle dia. 1.6mm - régulateur avec buse d'éjecteur dia. 1.6mm - regulador con boquilla eyector dia. 1.6mm
 18: valvola con ugello eiettore dia. 1.8mm - valve with injector nozzle dia. 1.8mm - régulateur avec buse d'éjecteur dia. 1.8mm - regulador con boquilla eyector dia. 1.8mm
 21: valvola con ugello eiettore dia. 2.1mm - valve with injector nozzle dia. 2.1mm - régulateur avec buse d'éjecteur dia. 2.1mm - regulador con boquilla eyector dia. 2.1mm
 23: valvola con ugello eiettore dia. 2.3mm - valve with injector nozzle dia. 2.3mm - régulateur avec buse d'éjecteur dia. 2.3mm - regulador con boquilla eyector dia. 2.3mm
 ES: valvola con dispositivo Energy Saving - valve with Energy Saving Device - régulateur avec dispositif Energy Saving - regulador con dispositivo Ahorro Energia