










# VALVOLE

VALVOLE DI SICUREZZA - SAFETY VALVES - SOUPAPES DE SÉCURITÉ - VÁLVULAS DE SEGURIDAD

CODICE CODE	Modello Model	Pressione Max Max Pressure		Portata - Flow		Attacco pompa Port size	Scarico By-pass	Peso - Weight			
		bar	psi	l/min	GPM			Kg	lbs		
	86.1670.00.2	VS 250	250	3600	24	6.3	3/8 BSP - F	3/8 BSP - F	0.36	0.8	
	86.1675.00.2	VS 250-2 BY-PASS 1/4	250	3600	24	6.3	Nº2 3/8 BSP - F	1/4 BSP - F	0.46	1.0	
	86.1660.00.2	VS 250-2 BY-PASS 3/8	250	3600	24	6.3	Nº2 3/8 BSP - F	3/8 BSP - F	0.46	1.0	
	86.1676.00.2	VS 350	350	5100	24	6.3	Nº2 3/8 BSP - F	3/8 BSP - F	0.46	1.0	
	ACCAIA INOX - STAINLESS STEEL	86.1677.00.2	VS 280 (AISI 303)	280	4000	80	21	Nº2 1/2 BSP - F	1/2 BSP - F	1.21	2.7
		86.1678.00.2	VS 400 (AISI 303)	400	5800	80	21	Nº2 1/2 BSP - F	1/2 BSP - F	1.21	2.7
	86.1679.00.2	VS 500	500	7250	80	21	1/2 BSP - F	1/2 BSP - F	1.42	3.1	
	86.1779.00.2	VS 180	180	2610	200	53	3/4 BSP - F	1/2 BSP - F	0.82	1.8	
	86.1680.00.2	VS 200	200	2900	450	119	1"1/4 BSP - F	1"1/4 BSP - F	3.8	8.4	
	74.1051.97.3	VS 750	720	10450	60	16	Rc3/8" - F	1/2" BSP - F	2	4.4	

Temperatura max: 90°C - 195°F - Max temperature: 90°C - 195°F - Température maxi: 90°C - 195°F - Temperatura máx: 90°C - 195°F